

CS-N1C | Chairman Unit



Description

CS-N1C can freely replace a variety of adaptive microphones. The newly developed voice control mode allows participants to start the microphone unit to speak without manual operation and speaking directly to the microphone. It is simple to use and fully applicable to various conference occasions.

Product Specification

Frequency Response:	50Hz-20KHz
Sensitivity:	-20dB+/-3dB(0dB=1V/Pa, f=1KHz)
SPL:	110dB(THD<5%, f=1KHz)
S/N(A weighted):	>100dBA(THD<1%, f=1 KHz)
Distortion:	<0.1%
Power Supply:	24V DC(supplied by the central controller)
Power Consumption:	0.72W
Unit Interface:	RJ45/CAT5 network port
Dimension (mm):	147 (L)×115 (W)×218 (H)
Weight:	Approximately 670g
Color:	Nickel black
Button:	Priority & On/mute

CS-N1D | Delegate Unit



Description

CS-N1D can freely replace a variety of adaptive microphones. The newly developed voice control mode allows participants to start the microphone unit to speak without manual operation and speaking directly to the microphone. It is simple to use and fully applicable to various conference occasions.

Product Specification

Frequency Response:	50Hz-20KHz
Sensitivity:	-20dB+/-3dB(0dB=1V/Pa,f=1KHz)
SPL:	110dB(THD<5%, f=1KHz)
S/N(A weighted):	>100dBA(THD<1%,f=1 KHz)
Distortion:	<0.1%
Power Supply:	24V DC(supplied by the central controller)
Power Consumption:	0.72W
Unit Interface:	RJ45/CAT5 network port
Dimension (mm):	147 (L)×115 (W)×218 (H)
Weight:	Approximately 670g
Color:	Nickel black
Button:	On/mute