

UR-222D

DUAL-CHANNEL ANTENNA DIVERSITY WIRELESS MICROPHONE SYSTEM



UR-222D Series of condensed the technology essence that Relacart accumulated over a long period. With advanced technology, sophisticated design, stable performance, with beautiful appearance, convenient operation and attractive price, with superior professional quality to win the market competition. This series is suitable for the nightclub of high requirements, multi-functional hall, hotel, conference room and small to medium performance.

Product Specification



UR-222D

Dual Channel Wireless Receiver

- EIA Standard Rack 1U metal rack receiver chassis, offering new style and simple LCD display;
- Bright LCD display can simultaneously display the working channel or frequency, RF & AF signal status, transmitter battery consumption as well as mute level.
- Antenna output with 8V DC

Main Frame Size:	EIA Standard Rack 1U
Channels:	Dual Channel
Frequency Stability:	±0.005% (-10°C~50°C)
Carrier Frequency Range:	521.25MHz~936.85MHz
Modulation Mode:	FM
Oscillation:	PLL synthesized
Receiving Sensitivity:	5dBμV, S/N>60dB at 25 deviation
Bandwidth:	32MHz
Max. Deviation Range:	±45KHz
S/N:	>105dB
T.H.D.:	<0.7%@1KHz
Frequency Response:	80Hz-18KHz ±3dB
Operating Range:	80M typical (in open space)
Power Supply:	DC 12V / 12W
Dimension (mm):	410(W)×206(D)×43(H)
Weight:	Approximately 1.9kg

Key Features



AFS(Automatic Frequency Selection)

- Press the "AFS" (Auto Frequency Selection) button 3 sec and the receiver will auto-scan and lock on to an open, interference-free frequency.



IR Infrared

- With [IR] infrared automatic frequency matching function, as long as the [SYNC] button is pressed, the transmitter can automatically and accurately lock the working frequency of the receiver.



Anti-Interference

- The stable PLL phase-locked oscillation circuit, combined with the "noise detection" mute control function, can effectively block the noise and radio frequency interference in the working environment.



Flexibility

- The handheld microphone: novel design, OLED display screen, showing battery level, working channel and frequency. The tube is made by durable alloy, effectively protecting the circuit element and battery rack, and with ergonomic grip.
- The new optimized circuit design, good sound quality, transmission distance is longer and more stable
- The capsule of handheld microphone can be removed and replaced, and the condenser or dynamic capsule can be used. It's compatible with SHURE SM-58 capsule. Using 6.3 mm unbalanced output and XLR balanced output synchronization output design, convenient to connect all kinds of audio processing equipment



Super Wide Frequency Range

- Ultra-wide frequency band UHF 522MHz~936 MHz, automatic frequency selection, CPU smart antenna diversity reception: 32 adjustable frequency points per channel, 64 adjustable frequency points in total for two channels, a total of 24 frequency bands can provide 768 adjustable frequency points for users to choose.



Univesal Property

- 134MHz broadband transmitter, the machines of four different frequency bands can be used interchangeably at will, which is convenient for debugging and management.



Environmental Protection and Energy Conservation

- Precise low-power circuit design makes the battery life twice as long as that of ordinary microphones.



UH-222

Wireless Handheld Microphone

- Handheld wireless microphone, simple design style, durable metal material, high contrast OLED display, built-in gain adjustment function, mute switch (optional mechanical switch). Microphone modular design, and various features of the capsule module optional, suitable for various occasions such as speech, singing, etc.

Carrier Frequency Range:	470MHz~936.85MHz
Oscillation:	PLL Synthesized
Harmonic Radiation:	<45dBm
Bandwidth:	134MHz(It depends on the region)
Max. Deviation Range:	±45KHz
Microphone Element:	Dynamic/Condenser(removable)
RF Output Power:	20mW/2mW
Battery:	Aax2
Current Consumption:	110mA(Typical)
Battery Current/ Life:	Approximately 11 hours
Microphone Lengths(mm):	52(Φ)×255(L)
Weight(w/o battery):	Approximately 235g



UT-222

Wireless Bodypack Transmitter

- bodypack-style wireless microphone, simple design, lightweight and practical engineering materials, durable, multi-function OLED display, built-in input selector switch, can be used to facilitate the instrument. The standard mini XLR microphone interface is suitable for a variety of well-known headset and clip microphones on the market. It is suitable for applications such as speech and singing.

Carrier Frequency Range:	470MHz~936.85MHz
Oscillation:	PLL Synthesized
Harmonic Radiation:	<45dBm
Bandwidth:	134MHz(It depends on the region)
Max. Deviation Range:	±45KHz
Input Connector:	4-pin mini-XLR connector
RF Output Power:	20mW/2mW
Battery:	Aax2
Current Consumption:	110mA(Typical)
Battery Current/ Life:	Approximately 11 hours
Microphone Lengths(mm):	84(H)×66(W)×23(D)
Weight(w/o battery):	Approximately 155g