

4PortGo | PORTABLE MULTICOUPLER FOR HCR-30D RECEIVERS



Description

4 Port Go is a Portable Multicoupler designed for live production. It can easily connect four HCR-30D true diversity wireless camera receiver systems, so as to provide multiple channels of audio transmission and management to recorders, cameras, mixers and other devices more conveniently without complicated entanglements. Provide balanced mini XLR audio output, The appearance is made of solid alloy, and the compact design can be put into the camera bag to carry with you, which is suitable for professional film and television production and outdoor shooting.

Product Specification

Frequency Range:	470 MHz – 960 MHz
Splitter Amplifier Gain:	0 dB, ± 3 dB (typical)
Antenna Power Supply (BNC A/B):	The display screen shows the current operating voltage of the system.
Maximum current:	150 mA (center pin positive)
Input/Output Impedance:	50 Ω
Audio Output Connectors:	8 $\times$ 3-pin mini XLR balanced audio outputs
DC Power Input:	DC IN: 8-12 V, 2 A
DC Power Output:	DC EXT: 10 V, 1 A
Battery:	Li-ion battery
Nominal Voltage:	7.4 V
Dimensions (mm):	260 (L) $\times$ 126.5 (W) $\times$ 88 (H)
Weight:	Approx. 1.5 kg