TS-N1F | GOOSENECK MICROPHONE DESK STAND



Description

- The TS-N1/TS-F1 is equipped with a blue/green LED indicator. The user can use the microphone to mute or speak operation, where the toggle between talk and mute can be programmed to toggle between live and mute audio (Latch switch on/off). Either preset to mute and only speak when pressed (press to talk), or preset to speak and only mute when pressed (press to mute).Low-impedance balanced audio output, the audio signal is output through the + and - pins of the XLR male header, and the G pin is connected to the ground (shield), and the output phase will be set on the + pin with a positive phase level.
- TS-N1:Matching microphone: GS-838/GS-450/EG-118/AL-19F/MS-923/MS-933
- TS-F1 : Matching microphone: GS-380/EG-118/AL-19F

Product Specification

Frequency Response:	50Hz~20KHz
Impedance:	250Ω
Dynamic Range (typical):	100dB, 1KHz at maximum sound pressure
S/N ratio:	110dB, 1KHz at 1% T.H.D.
Switch:	On/Mute
Power Supply:	DC 24-52V phantom power supply
Output Connector:	phoenix terminal connector/ euroblock
Weight:	700-720 g
TS-N1: Input socket:	3-pin XLR male socket
TS-F1: Input socket:	3-pin XLR female socket
Accessories Furnished:	Windscreen
Color:	Black