

4PortGo | PORTABLE MULTICOUPLER FOR HCR-30D RECEIVERS



Description

4 Port Go is a Portable Multicoupler designed for live production. It can easily connect four HCR-30D true diversity wireless camera receiver systems, so as to provide multiple channels of audio transmission and management to recorders, cameras, mixers and other devices more conveniently without complicated entanglements. Provide balanced mini XLR audio output, The appearance is made of solid alloy, and the compact design can be put into the camera bag to carry with you, which is suitable for professional film and television production and outdoor shooting.

Product Specification

Frequency range:	470MHz-960MHz
Distribution Gain:	0dB,±3dB (typical)
Antenna Power:	Displays the system's current operating voltage. Max. current: 150 mA (center-positive)
Maximum power:	24 W
DC power input:	DC 7-18 V / 2 A
DC power output:	DC 10-18 V / 1 A
Battery Type:	NP-F Series batteries: NP-F550 to NP-F970, nominal Voltage: 7.4 V
Device Capacity:	Up to four portable plug-in receivers
Operating Temperature:	-10°C to +55°C, 95% RH
Storage Temperature:	-20°C to +65°C, 95% RH
Dimensions (mm):	240 (W) × 140 (W) × 90 (H)
Net Weight:	1.5 kg