



CS-100 is a practical and economical conference discussion system, elegant appearance, convenient installation, simple operation, widely apply to boardrooms, business meetings, educational institutions, hotels, conference rental, system reconstruction, etc.

## Product Specification

- EIA Standard Rack 1U metal chassis;
- Equipped with handle, easy for lift or move.

Main Voltage:	100V-240V AC 50/60Hz
50W	
Current Consumption:	45W
Static Power:	500mW
Frequency Response:	55Hz-17KHz±2dB
S/N:	>90dB
Distortion(T.H.D):	<0.3%
Output Power:	15W/12V(Each Channel)
RCA Input:	-9dBV(f=1KHz,THD<0.3%)
XLR Output:	-10dBV
Unbalanced Line Output(6.3mm jack):	-15dBV
RCA Output:	-3dBV
Chairman/Delegate Unit Interface	Anti drop 9P aviation plug
Dimension(mm):	410(W)×206(D)×43(H)
weight(kg):	2.3



**CS-100M**  
Central Controller



**CS-100C**  
Chairman Unit

- Advanced conferencing technology, compliant with ICE60914.
- Unidirectional condenser microphone for high quality sound pickup.
- Anti-drop aviation cable, hand in hand connection way, simple connection, reliable and convenient for set up.
- Priority bottom to switch off the speaking unit.
- With illuminated ring to indicate the working status;
- Black or silver for selection.

Main Voltage:	DC24 V
Polar Pattern:	Cardioid Condenser
Power Consumption:	110mA
Frequency Response:	65Hz-18KHz
S/N:	>90dB
Distortion(T.H.D):	<0.7%
Sensitivity:	-20dBv /Pa
Chairman/Delegate Unit Interface:	Anti-drop 9P aviation plug
Microphone Length: (Selectable)	340mm/420mm(default) /480mm
Tabletop Size(mm): (without microphone)	105(W)×150(D)×43(H)
weight(g):	780g
Color:	Nickel black



**CS-100D**  
Delegate Unit

- Advanced conferencing technology, compliant with ICE60914.
- Unidirectional condenser microphone for high quality sound pickup.
- Anti-drop aviation cable, hand in hand connection way, simple connection, reliable and convenient for set up.
- Priority bottom to switch off the speaking unit.
- With illuminated ring to indicate the working status;
- Black or silver for selection.

Main Voltage:	DC24 V
Polar Pattern:	Cardioid Condenser
Power Consumption:	110mA
Frequency Response:	65Hz-18KHz
S/N:	>90dB
Distortion(T.H.D):	<0.7%
Sensitivity:	-20dBv /Pa
Chairman/Delegate Unit Interface:	Anti-drop 9P aviation plug
Microphone Length: (Selectable)	340mm/420mm(default) /480mm
Tabletop Size(mm): (without microphone)	105(W)×150(D)×43(H)
weight(g):	780g
Color:	Nickel black

## Key Features



### Clear Sound Quality

- Unidirectional condenser microphone for high quality sound pickup.
- Equipped with auto-gain audio process circuit, effective prevent the feedback.
- Built-in high performance processor, enable auto-process system gain, control feedback.



### Flexible Speech

- Active 1/3/6 microphones in a time, AUTO speaking mode, chairman unit has the priority to override all delegate units.



### Anti-Interference

- Special 9-pin aviation connection cable, effectively minimize the interference.



### Flexible Expansion

- Can connect up to 60 microphone units.
- Audio input function, enable to connect to the external audio equipment.
- Connecting the telephone coupler can apply to the remote telephone conference directly.

## Application:

