

Mi2.PRO

2.4G DUAL CHANNEL WIRELESS MICROPHONE SYSTEM



Relacart MIPASSPORT Mi2.PRO is a lightweight, portable, fully functional, easy-to-operate, 2.4GHz dual-channel wireless microphone system with onboard high-quality recording function, providing excellent developed such as DSLRs, camcorders, smartphones, tablets or computers. It is ideal for interviews, live broadcasts, Vlog shoots or business presentations.

Key Features



Widely Compatible

- Widely compatible with digital or SLR cameras, smartphones, tablets, mobile devices and more



Save Recording Audio

- Recording and listening while saving, to ensure flawless audio output.



Flexible Expansion

- Built-in electret microphone, also supports external alvalier microphone, output volume can be adjusted.



2.4g ISM Global Unlimited Frequency Band

- Adopts 2.4G ISM global unlimited frequency band transmission.



Real-time Monitoring

- Dual channel receiver with USB audio output port and 3.5mm output port, the receiver also has a live monitoring headphone port.



Convenient Design

- Adopts a high-brightness OLED display, which clearly shows the working status.
- The body is small and easy to carry
- Automatic pairing at startup
- Built-in lithium battery, charging with USB 5V
- The 3.5mm TRS output is used to connect to digital / SLR cameras, camcorders, recorders, tablets, mobile phones and other devices to assist in picking up high fidelity Audio for interviews, micro-video recordings, or business presentations.

MIPASSPORT 2.4G ULTRA-COMPACT WIRELESS MICROPHONE SYSTEMS

Product Specification



Mi2. PRO

Dual Channel Wireless Microphone System

Transmission Frequency Band:	2400MHz ~ 2483.5MHz
Audio Frequency Response:	100Hz ~ 18KHz ± 3dB
Dynamic Range:	95dB (Circuit performance)
S/N:	95dB (Circuit performance)
SPL:	100dB(built-in microphone)
Pairing Type:	Automatic
Effective Working Distance:	20m(there is block) 50m(in open space)
Working Temperature:	-5°C to + 50°C



Mi2. PRO

Wireless Receiver

Transmission Frequency Band:	2400MHz ~ 2483.5MHz
Transmission Type:	Frequency Hopping/Digital GFSK
Receiving Sensitivity:	-94dBm
Antenna Method:	Built-in F type antenna
Display Mode:	OLED display, showing current status
Power Requirements:	Built-in lithium battery, standard USB 5V charging via Type-C interface
Battery Life:	≤8 hours
Output Interface:	3.5mm TRS
Headphone Monitor Output:	Yes
Working Temperature:	-5°C~+50°C
Dimensions (mm):	50 ×44.5×15
Weight:	35g



Mi2. PRO

Wireless Transmitter

Transmission Frequency Band:	2400MHz ~ 2483.5MHz
Modulation Type:	Frequency Hopping/Digital GFSK
Transmit Power :	10dBm
Antenna Method :	Built-in F type antenna
Recording Function :	On-board SD NAND
Microphone Pickup Method:	Omnidirectional (built-in Mic and external lavalier)
Internal Storage :	32GB
Recording File Format :	WAV
Display Mode:	OLED display, showing current status
Power Requirements:	Built-in lithium battery, standard USB 5V charging via TYPE-C interface
Battery Life:	≤8 hours
Output Connector:	3.5mm TRS
Working Temperature:	-5°C to + 50°C
Dimensions (mm):	50 ×44.5×15
Weight:	35g