

AL-19N/19T/19F | Gooseneck Microphone



Description

AL serie goonseneck microphone is a wide-range miniature condenser microphone with a cardioid polar pattern and an integral low cut switch. It is designed for quality sound reinforcement, professional recording, elevison and other demanding sound pickup applications. The small-diameter, alternating adjustable-length gooseneck design permits highly flexible positioning while maintaining a smooth, well-contoured appearance. An included snap-on foam windscreen effectively reduces wind noise and "popping". The integral power module can be powered from any external 11 V to 52V DC phantom power supply.

Product Specification

Capsule Type:	Condenser
Polar Pattern:	Cardioid
Frequency Response:	80Hz~18KHz
High Pass Filter:	100Hz, 18dB/octave
Turn-on Sensitivity:	-32dB, at 1V at 1Pa
Impedance:	200Ω
SPL:	127 dB, 1KHz at 1% T.H.D
Dynamic Range(Typical):	110dB, 1KHz at max. SPL
Switch:	Flat, high pass filter
S/N Ratio:	>68dB, 1KHz at 1Pa
Phantom Power Requirements:	11-52V DC
Consumption:	5mA typical
Dimensions/Weight:	AL-19N: 380mm ,150g AL-19T: 450mm , 170g AL-19F: 530mm , 190g
Output Connector :	Male 3-pin XLR
Best Distance for Sound Pickup:	10cm-20cm
Color:	Black